

CHAPTER 165

LOW-COST SHORELINE PROTECTION

Billy L. Edge,¹ John G. Housley,² and George M. Watts³

ABSTRACT

As the public interest in low-cost, self-installed solutions to shoreline erosion continues to grow, the involvement of private enterprise in developing solutions intensifies. Now that low-cost devices are identified as a salable commodity as goods or services, the number of inventors, creative engineers, agronomists, and foresighted planners producing potential designs are rapidly growing. Over two hundred devices, both proven and untested devices, have been cataloged as a part of the National Shoreline Erosion Demonstration Program. This program calls for the Corps of Engineers to plan, establish, and conduct for a period of five years a shoreline erosion control development and demonstration program including physical and vegetative devices.

INTRODUCTION

There is no need to recount the tales of the thousands of miles of eroding shoreline around the United States as well as throughout the world; the National Shoreline Study adequately covers the discouraging situation around the coastline of the United States. Little else needs to be said to emphasize that without adequate protection, in the broadest sense, a very significant part of our coastline falls prey to the ravages of the sea, and, of course, to man himself. Adequate protection against these forces comes normally by constructing monumental structures, such as the San Francisco seawall (O'Shaunessy), which render the land-sea-air interface permanent. It is definitely not in the best interest of the nation to provide this degree of protection at other than very valuable property at an extremely high wave energy site.

¹Associate Professor of Civil Engineering, Clemson University, Clemson, South Carolina 29631 and Vice-Chairman Shoreline Erosion Advisory Panel.

²Civil Engineer, Planning Division, Directorate of Civil Works, Office of Chief of Engineers, U.S. Army Forrestal Building, Washington, D.C. 20314.

³Chief, Engineering Development Division, U.S. Army Coastal Engineering Research Center, Fort Belvoir, Virginia 20060.

At the opposite extreme of the cost scale is the institutional type of protection. Through appropriate legislation and other forms of institutional arrangements, loss of man-made structures along the shoreline is prevented. By restricting development to behind the third row of dunes (McHarg), man-made structures are protected from falling to the forces of the sea, at least for several years, and at the same time with adequate control the dune structure is maintained for the last line of defense. There is much to be said for this form of protection in an area that is not already fully or even overdeveloped. In the latter case it makes pitifully little sense to legislate shoreline protection. Rather, recognizing that there is little man can do to completely stop erosion, attention must be given to providing erosion protection in the form of a new beach equilibrium--a form which does not match the energy of the ocean against the inertia of a coastline but a form which enhances the resistance of the shore to erosion.

Within the context of the philosophy sketched here shoreline protection can be a reality and not a dream. Moreover, within the broad spectrum of solutions available, from laws to monuments, there is a place for low-cost protection.

Whenever major erosion threatens public property, astute elected officials generally call upon state or federal government to help solve the problem. On the other hand, when the property is private, help is seldom available and the owner is forced to provide his own defense. This requirement often results in many thousands of dollars being wasted by construction of ill-conceived projects. Sometimes the owner goes to a coastal engineer for help; but, more frequently, they design their own protection with the "good advice" of a brother-in-law, uncle, or helpful neighbor. Unfortunately, even if the private landowner does come to a coastal engineer, he seldom receives the kind of inexpensive advice for which he is looking. This is not necessarily the fault of the coastal engineer since the type of protection with which he is normally concerned is of the more glamorous, permanent, and expensive variety. So the home owner, dejected by the exorbitant costs of the traditional shore protection works, is faced with paying more than he can or is willing to afford, selling his property to an unsuspecting buyer, or developing his own solution.

More recently, significant interest has arisen in the governmental and industrial sectors to provide help for the private landowner with an eroding shoreline. Some research has been sponsored by state and federal government, although not at a level commensurate with the problem. A major demonstration and testing program has been undertaken by the Michigan Department of Natural Resources (Brater, Armstrong, and McGill, 1974, 1975). The demonstration projects are designed to provide data on various devices, methods of construction, and costs. Close evaluation of the results of this study will provide extremely useful information on effectiveness and durability of each of these shore protection devices.

Significant efforts have also been made to educate the public about not only devices suitable and available but more fundamentally about the

basic phenomena that cause erosion problems (Brater). These publications range from brochures or "roadmaps" (Arno) to thorough treatments in the language of the intended user (Habel). This self-help literature has been distributed widely in the Great Lakes area and less completely in the Atlantic, Gulf, and Pacific areas with the hope of improving on the landowners self-design.

Industry is responding to the need for low cost solutions through their own research and development which is providing the coastal engineer with many new and innovative ideas that "might" fall into the category of low cost.

Before going further, a few words of clarification are in order. It is not implied that a "low-cost" solution is acceptable or even available for most erosion situations; rather the emphasis of this paper is on eroding areas that are not necessarily amenable to the more-costly, traditional forms of control. Moreover, it must be pointed out that too often the inexpensive methods of protection are not "low-cost" at all.

To evaluate the new concepts and ideas for low-cost protection and to disseminate the results to the owners of eroding shorelines, the U.S. Congress created the National Shoreline Erosion Demonstration Program.

Section 54 of the "Shoreline Erosion Control Demonstration Act of 1974," directed the Secretary of the Army, acting through the Corps of Engineers to establish and conduct for a period of five years a national shoreline erosion control and demonstration program. The intent of the program is to develop and demonstrate to the public and technical community methods for "low-cost" shore protection. Specifically, these methods are to be developed and demonstrated in "sheltered waters." Sheltered waters are defined as those areas where the design breaking wave is less than six feet. In addition, the Act specifically calls for widespread dissemination of the results of this program.

In the following sections, proven methods and devices for low-cost protection is discussed. Next, several of the new and innovative and yet untried concepts are presented. The National Shoreline Erosion Demonstration Program is presented in terms of direction, accomplishments, and goals.

What constitutes low-cost shore protection? This question is addressed here to provide the framework needed for further discussion. Low-cost shore protection is shore protection for sheltered or inland areas which fulfills one of the following criteria:

- a. Cost less than \$50 per front foot for materials and can be constructed without the use of heavy construction equipment.
- b. Cost less than \$125 per front foot for materials plus placement using heavy construction equipment.

These cost figures are intended to provide a degree of protection to the shore for approximately a 10-year period with a minimum of maintenance assuming that a storm exceeding a 1 in 25 year severity is not encountered during the 10-year interval with the severity being measured in terms of a combination of violence and duration.

This definition now raises the question, what is a sheltered area? For the purpose of low-cost protection it is defined as follows. A "sheltered" or "inland" site is an area which falls under one or more of the following conditions:

Coastal shores. Those shores receiving wave attack from waves generated on the open or semi-open waters of the Atlantic, Gulf, Pacific, Bering Sea, or Arctic Ocean, but which waves are attenuated by refraction, diffraction or friction in such a manner that the significant wave height of waves breaking on these shores never exceeds six feet in height.

Tidewater shores. Those shores fronting on the inland tidal waters connected with the Atlantic, Gulf, Pacific, Bering Sea, or Arctic Ocean.

Great Lakes shores. All shores fronting on the Great Lakes plus the shores of all bays connected directly with one of the Great Lakes and standing at the same water levels as the parent Great Lake.

DEVICES AND METHODS WITH POTENTIAL FOR SUCCESS

This section is devoted to describing devices and methods which, if used in the field, would result with a high probability of success. This description is not intended to be all inclusive but rather to present those concepts and established devices which have a probable chance of success. Devices can be categorized as follows:

- Revetments
- Seawalls
- Bulkheads
- Breakwater
- Beach fills
- Groins
- Vegetation
- Institutional

There is one extremely important factor concerning the successful behavior of all gravity, and to some extent cantilevered, type structures in the above list. This factor involves an adequate foundation and toe (most seaward portion) protection for the structure. The successful behavior of any gravity structure whether it be semi-flexible or rigid is very much dependent on the adequacy of foundation materials on which the structure is placed. If the foundation is inadequate or under-designed, a high degree of movement of structural components can be expected with resultant failure of the integrity of the structure. A properly designed and constructed foundation for the overlying structure can result in a satisfactory performance equal to or greater than the desired life of the installation, assuming, of course, the structural components of the main element of the structure are properly designed.

Revetments

Substantial data are available to verify that a graded rip-rap type revetment can be very successful as a shore stabilization structure. Of course, the stone size distribution in the revetment, including the foundation material, must be commensurable with expected wave forces on the structure.

In geographic areas where the cost of placing suitable rip-rap material (stone) exceeds acceptable limits, consideration could be given to the placement of precast concrete armor units on a proper foundation. Most all of the presently used precast armor units are described in the CERC Shore Protection Manual. The use of precast concrete units is generally associated with large coastal structures subjected to very large wave forces. However, there are no apparent technical reasons why small precast concrete armor units, would not be equally effective in a low wave energy environment.

There are other alternative materials and approaches for construction of revetments which exhibit potential success; however, presently available performance data in regard to upper limit of stability are meager and

this lack of information is influential in establishing the relative probability of success if the structure is tested in the demonstration program. These alternatives include the precast concrete interlocking and semi-interlocking units placed on a proper foundation and appropriate toe protection provided. Also, included is a step-type revetment consisting of cribbing units which are interlocking and filled with proper graded stones, all placed on an adequate foundation with toe protection provided in front of the first step. However, one factor of concern for the crib type revetment involves a prediction of the durability of the cribbing units if low-cost constraints are adhered to for its structural make-up.

Seawalls and Bulkheads

The primary function of a seawall is to protect the area behind it from direct wave attack and the structure may or may not be subjected to backfill pressures. Bulkheads' functions are to retain backfill and are subjected to direct wave attack. The functional difference between a seawall and a bulkhead is, therefore, sometimes difficult to delineate, but for purposes of application in moderate to low wave energy environments, they may be considered to serve the same function with seawalls and, therefore, would generally be more massive than bulkheads.

There are a number of existing designs of precast concrete type seawalls, if placed on an adequate foundation, that would be promising for success. Most of these designs would require heavy equipment to handle and place the concrete segments. Promising results could also be obtained for a seawall constructed of cribbing filled with stones with the structure placed on a proper foundation and toe protection provided. However, the factor concerning structural durability of the cribbing for the seawall would be similar to that cited for the cribbed type revetment mentioned earlier.

The presently available technical guidance on bulkhead design is somewhat substantial, therefore, installation of a standard steel, concrete, or timber sheetpile bulkhead as a low-cost structure would most likely be successful. Appropriate measures to prevent excessive wave induced bottom scour in front of the sheetpile is necessary or desirable for most installations. There are alternative sheetpiling materials that would be considered for the bulkheading and depending on local environmental conditions (mainly physical). These may prove to be cost effective and exhibit a high probability of success. Examples of such materials are aluminum, asbestos, fiberglass, and many variations of synthetics. The use of lightweight steel or special additives to concrete to reduce weight but maintain strength, and thus reduce material costs of the sheetpiling, would also seem appropriate to consider.

Breakwaters

There has been limited use of breakwaters in the United States for strictly shore protection purposes. Since these structures are located offshore at depths commensurable with desired beach and shore responses, they are subjected to greater wave forces and structural components must

be stronger or larger than for those structures located in the foreshore or beach zone. An offshore breakwater of proper design will dissipate incident wave energy, thus, the shores within the "lea or shadow" of the breakwater will be protected, and in this context the overall functional behavior of the structure could be considered as promising with regard to success. There are two basic or standard techniques to constructing offshore breakwaters, both of which could be considered as resulting in a high probability of success if constructed in the demonstration programs. The first involves the use of rubble with an armor layer of stone or precast concrete units, depending on economics; and, the second involving the use of semi-interlocking precast concrete segments. Each technique requires provision for an appropriate foundation to support the super-structure, including toe protection which will remain stable under design wave forces. Relatively heavy-duty equipment and possibly certain marine plants are required for most breakwater construction and since the structure is located offshore, it is apparent that construction practices and procedures are more difficult and involved as compared to construction of a similar structure on the shore zone. This is particularly important to keep the project within the low-cost category.

Considerable attention has been given to the use of portable or floating breakwaters to attenuate wave energy. There are currently no devices of this type that do not become less efficient in wave energy attenuation as the wave length of the incident wave increases. The fact that low-cost solutions generally will be confined to sheltered waters does introduce an attraction to utilize floating breakwater devices as short wave periods would normally prevail.

Beach Fill

The use of beach fill as a low-cost structure would result in a probable chance of success provided the placed fill was of suitable size characteristics. Periodic nourishment for the initially placed fill would be required or should be anticipated. The predominance of short period waves breaking on the beach fill means that direct offshore transport will dominate. No beach recovery can be expected by onshore transport since, in general, there would be no, or minimal, occurrences of long period waves; thus, periodic nourishment to balance the losses to the offshore zone would be necessary to maintain desired project dimensions in the study area. Depending on local conditions, terminal structures (groins) may be needed at one or both ends of the eroding segment, as well as, artificial headlands.

Groins

An accurate determination of the littoral material movement of the site specific is essential to the use of groins as a low-cost structure. A moderate amount of alongshore transport of littoral materials must prevail in the area or a groin or groin system will not function properly. Assuming the prevailing littoral material transport conditions are favorable for the functional aspects of a groin system, there are several materials from which the groins can be constructed and successful results

expected. Constructing the groin of rubble has several desirable features in regard to wave energy dissipation and retention of the impounded sand. This assumes the structure has a proper foundation and distribution of stone throughout the groin cross-section. The use of steel, concrete or timber sheetpiling with stone protection around the outer end is also a well-proven and acceptable method for groin construction. Pre-fabricated segments (concrete) which have an interlocking or semi-interlocking design and founded on a proper foundation can also be structurally effective. If the material components of a crib type structure (crib units filled with stone) will be durable for the life of the structure, there is no reason to believe this type of groin would not also be effective.

If the site conditions are favorable for testing of a groin system, the most effective structure would be a rubble design. The performance of a sheetpile design with rubble placed around the outer end of the groin should be comparable to a prefabricated segmented design (interlocking or semi-interlocking) placed on proper foundation materials.

Vegetation

Very little information and guidance are presently available in regard to the effectiveness of vegetation to directly dissipate incident wave energy. Its effectiveness in a high wave energy environment is probably very limited. On the other hand, the use of vegetation to impound or retain aeolian sand in the foredune area of the coastal zone is well proven and these stabilized or created foredunes are of tremendous value in terms of shore protection.

Fairly adequate data are available on species adaptation and on establishment and maintenance on the Atlantic and Gulf Coasts. On the Great Lakes, Pacific and Alaskan coasts, considerably less is known. Although vegetation is the only generally accepted method to feasibly stabilize dunes, few quantitative estimates are available on the degree of protection provided. Dahl et al. gives a very complete literature review. Recent successes using panic grass (Panicum amarum) along the North Carolina Coast in dune stabilization is given by Seneca, Woodhouse and Broome. In addition to panic grass, American beachgrass, european beachgrass, and sea oats are some of the more successful vegetation used in dune building and stabilization.

The intertidal zone has not yet received the same degree of success. However, vegetation appears to offer considerable promise for the more protected site. Considering that many thousands of miles of shoreline are now well protected by natural marsh grass, it is obvious that the most likely technique for stabilizing the shoreline in a sheltered area is to simulate the protection provided by nature. With some assistance by man through planting sufficient numbers of plants or seeds, at the proper time, the invasion of natural marsh species can be hastened. Most of the work done in the intertidal zone has been with smooth cordgrass (Spartina alterniflora). This plant thrives well in the intertidal salt marshes of the Atlantic and Gulf Coasts. In the more brackish waters the following grasses are being considered: three-square (Scirpus Americanus), needle rush grass (Juncus roemerianus), and saltmeadow cordgrass (Spartina patens). Very little

has been written on the degree of protection that this method can provide although there is much current research in this area. Webb and Dodd show how smooth cordgrass has been used in Galveston Bay. It appears though that marsh vegetation in conjunction with some form of physical temporary protection, such as a floating breakwater, offer much opportunity for low-cost shoreline protection at a very attractive cost.

Institutional Devices

Intangible devices are much more difficult to identify except in a generic sense. Moreover, the actual cost of institutional devices are ill defined. Conceptually, the ideas that can be considered in this category include zoning, permitting, taxing and such other regulatory powers that government - local, state, and federal - can use. The institutions in themselves are indeed low-cost; however, the cost of implementing the regulation to the property owner can be quite costly. For example, if a land owner were experiencing a rapid rate of erosion he would want to quickly install some device to slow or stop the process. However, if a coastal zone authority does not permit the use of structures within fifty feet of the mean high water line then the land owner will not be allowed to protect his property and thus his cost will in no way be low. Yet, the cost to the coastal zone authority is minimal. In brief, there are few, if any, institutional devices that could qualify, to the individual homeowner, as low-cost shoreline protection.

INNOVATIVE DEVICES

As the public interest in low-cost, self-installed solutions to shoreline erosion continues to grow, the involvement of private enterprise in developing solutions intensifies. Now that low-cost devices are identified as a salable commodity as goods or services, the number of inventors, creative engineers, agronomists, and foresighted planners producing potential designs are rapidly growing. This energy has and continues to lead to very innovative designs that may be functionally and structurally successful and may be low-cost. As a part of the National Shoreline Erosion Demonstration Program, known devices and methods which have been used or tested in various degrees, or just proposed, have been tabulated. The list is limited to just those items which might be classified as low-cost. A page from that list is included as Figure 1. The devices have been categorized as shown below along with the number of devices in each category.

Revetments	37
Bulkheads and seawalls	35
Groins	39
Offshore breakwaters	24
Floating breakwaters	18
Beach fills	9
Coastal vegetation	27
Other	8

From this compilation of devices, the Shoreline Erosion Advisory Panel (which will be described later in this paper) has recommended that from this list of devices at least the following should be field tested.

- Aluminum bulkheads
- Bins or cribs (concrete, steel, aluminum, or wood)
- Gabions (rusting of mesh container a problem)
- Longard tubes (sand-filled plastic tubes)
- Nami rings (upright concrete culvert pipe)
- Interlocking concrete block (with filter cloth)
- Stone rip-rap (with gravel or plastic filters or mastic binder)
- Plastic bags (sand filled or concrete filled)
- Precast concrete sheet piling (possibly pre-stressed)
- Rubble mound groins and breakwaters
- Concrete pipe groins
- Z-wall offshore breakwaters (steel or concrete)
- Scrap tire floating breakwater
- Tethered floating mat plastic breakwaters

It was further recommended that existing installations of the following devices should be monitored.

- Sand-grabber (cinder blocks)
- Shore-protector (slat breakwater)
- Beach-builder (flap valve breakwater)

Figures 2-9 show examples of several forms of low-cost structures that have been proposed or used in the field. Some of these devices hold great promise while others do not appear as attractive.

SHORE EROSION ADVISORY PANEL
 INFORMATION ON EROSION CONTROL DEVICES - METHODS
 CATEGORY D - OFFSHORE BREAKWATERS

Ref. No.	Description of Device	Results of Laboratory Tests				Results of Field Installations										Project Data	Comments (CIPA or IFAF Review)																																																																																																																																																																																																																																																												
		Test Location	Test Period	Wave Height	Wave Period	1/2 Wave Height	1/4 Wave Height	1/8 Wave Height	1/16 Wave Height	1/32 Wave Height	1/64 Wave Height	1/128 Wave Height	1/256 Wave Height	1/512 Wave Height	1/1024 Wave Height			1/2048 Wave Height	1/4096 Wave Height	1/8192 Wave Height	1/16384 Wave Height	1/32768 Wave Height	1/65536 Wave Height	1/131072 Wave Height	1/262144 Wave Height	1/524288 Wave Height	1/1048576 Wave Height	1/2097152 Wave Height	1/4194304 Wave Height	1/8388608 Wave Height	1/16777216 Wave Height	1/33554432 Wave Height	1/67108864 Wave Height	1/134217728 Wave Height	1/268435456 Wave Height	1/536870912 Wave Height	1/1073741824 Wave Height	1/2147483648 Wave Height	1/4294967296 Wave Height	1/8589934592 Wave Height	1/17179869184 Wave Height	1/34359738368 Wave Height	1/68719476736 Wave Height	1/137438953472 Wave Height	1/274877906944 Wave Height	1/549755813888 Wave Height	1/1099511627776 Wave Height	1/2199023255552 Wave Height	1/4398046511104 Wave Height	1/8796093022208 Wave Height	1/17592186044416 Wave Height	1/35184372088832 Wave Height	1/70368744177664 Wave Height	1/140737488355328 Wave Height	1/281474976710656 Wave Height	1/562949953421312 Wave Height	1/1125899906842624 Wave Height	1/2251799813685248 Wave Height	1/4503599627370496 Wave Height	1/9007199254740992 Wave Height	1/18014398509481984 Wave Height	1/36028797018963968 Wave Height	1/72057594037927936 Wave Height	1/144115188075855872 Wave Height	1/288230376151711744 Wave Height	1/576460752303423488 Wave Height	1/1152921504606846976 Wave Height	1/2305843009213693952 Wave Height	1/4611686018427387904 Wave Height	1/9223372036854775808 Wave Height	1/18446744073709551616 Wave Height	1/36893488147419103232 Wave Height	1/73786976294838206464 Wave Height	1/147573952589676412928 Wave Height	1/295147905179352825856 Wave Height	1/590295810358705651712 Wave Height	1/1180591620717411303424 Wave Height	1/2361183241434822606848 Wave Height	1/4722366482869645213696 Wave Height	1/9444732965739290427392 Wave Height	1/18889465931478580854784 Wave Height	1/37778931862957161709568 Wave Height	1/75557863725914323419136 Wave Height	1/151115727451828646838272 Wave Height	1/302231454903657293676544 Wave Height	1/604462909807314587353088 Wave Height	1/1208925819614629174706176 Wave Height	1/2417851639229258349412352 Wave Height	1/4835703278458516698824704 Wave Height	1/9671406556917033397649408 Wave Height	1/19342813113834066795298816 Wave Height	1/38685626227668133590597632 Wave Height	1/77371252455336267181195264 Wave Height	1/154742504910672534362390528 Wave Height	1/309485009821345068724781056 Wave Height	1/618970019642690137449562112 Wave Height	1/1237940039285380274899124224 Wave Height	1/2475880078570760549798248448 Wave Height	1/4951760157141521099596496896 Wave Height	1/9903520314283042199192993792 Wave Height	1/19807040628566084398385987584 Wave Height	1/39614081257132168796771975168 Wave Height	1/79228162514264337593543950336 Wave Height	1/158456325028528675187087900672 Wave Height	1/316912650057057350374175801344 Wave Height	1/633825300114114700748351602688 Wave Height	1/1267650600228229401496703205376 Wave Height	1/2535301200456458802993406410752 Wave Height	1/5070602400912917605986812821504 Wave Height	1/10141204801825835211973625643008 Wave Height	1/20282409603651670423947251286016 Wave Height	1/40564819207303340847894502572032 Wave Height	1/81129638414606681695789005144064 Wave Height	1/162259276832213363391578010288128 Wave Height	1/324518553664426726783156020576256 Wave Height	1/649037107328853453566312041152512 Wave Height	1/1298074214657706907132624082305024 Wave Height	1/2596148429315413814265248164610048 Wave Height	1/5192296858630827628530496329220096 Wave Height	1/10384593717261655257060992658440192 Wave Height	1/20769187434523310514121985316880384 Wave Height	1/41538374869046621028243970633760768 Wave Height	1/83076749738093242056487941267521536 Wave Height	1/166153499476186484112975882535043072 Wave Height	1/332306998952372968225951765070086144 Wave Height	1/664613997904745936451903530140172288 Wave Height	1/1329227995809491872903807060280344576 Wave Height	1/2658455991618983745807614120560689152 Wave Height	1/5316911983237967491615228241121378304 Wave Height	1/10633823966475934983230456482242756608 Wave Height	1/21267647932951869966460912964485513216 Wave Height	1/42535295865903739932921825928971026432 Wave Height	1/85070591731807479865843651857942052864 Wave Height	1/170141183463614959731687303715884105728 Wave Height	1/340282366927229919463374607431768211456 Wave Height	1/680564733854459838926749214863536422912 Wave Height	1/1361129467708919677853498429727072845824 Wave Height	1/272225893541783935570699685945414569152 Wave Height	1/544451787083567871141399371890829138304 Wave Height	1/1088903574167135742282798743781658276608 Wave Height	1/2177807148334271484565597487563316553216 Wave Height	1/4355614296668542969131194975126633106432 Wave Height	1/8711228593337085938262389950253266212864 Wave Height	1/17422457186674171876524779900506524525728 Wave Height	1/34844914373348343753049559801013049051456 Wave Height	1/69689828746696687506099119602026098102912 Wave Height	1/139379657493393375012198233204052196205824 Wave Height	1/278759314986786750024396466408104392411648 Wave Height	1/557518629973573500048792932816208784823296 Wave Height	1/1115037259947147000097585865632417569646592 Wave Height	1/2230074519894294000195171731264835139293184 Wave Height	1/4460149039788588000390343462528670275966368 Wave Height	1/8920298079577176000780686925057340551932736 Wave Height	1/17840596159154352001561373850114681103865472 Wave Height	1/35681192318308704003122747700229362207730848 Wave Height	1/7136238463661740806244549540045872441546176 Wave Height	1/14272476927323481612489099080091744883092352 Wave Height	1/2854495385464696322497819816018348976618464 Wave Height	1/5708990770929392644995639632036697953236928 Wave Height	1/11417981541858785299991279264073395906473856 Wave Height	1/22835963083717570599982558528146791812947712 Wave Height	1/45671926167435141199965117056293583625895424 Wave Height	1/91343852334870282399930234112587167251790848 Wave Height	1/182687704669740564799860468225174334503581696 Wave Height	1/36537540933948112959972093645034866900716392 Wave Height	1/73075081867896225919944187290069733801432784 Wave Height	1/146150163735792451839888374580139467602865568 Wave Height	1/292300327471584903679776749160278935205731136 Wave Height	1/584600654943169807359553498320557870411462272 Wave Height	1/1169201309886339614719106996641115740822924544 Wave Height	1/2338402619772679229438213993282231481645849088 Wave Height	1/4676805239545358458876427986564462963291698176 Wave Height	1/9353610479090716917752855973128925926583396352 Wave Height	1/18707220958181433835505711946257853953166792704 Wave Height	1/37414441916362867671011423892515707906333585408 Wave Height	1/74828883832725735342022847785031415812667170816 Wave Height	1/149657767665451470684045695700062831625333416332 Wave Height	1/299315535330902941368091391400125663250666832664 Wave Height	1/598631070661805882736182782800251325001336655328 Wave Height	1/1197262141323611765472365565600502650002673106656 Wave Height	1/2394524282647223530944731131201005300005342133312 Wave Height	1/478904856529444706188946226240201060001068266624 Wave Height	1/9578097130588894123778924524804021200021365333248 Wave Height	1/1915619426117778824755784904968042400004530666656 Wave Height	1/383123885223555764951156980993608480000907333312 Wave Height	1/7662477704471115299023139619872169600018146666624 Wave Height	1/15324955408942230598046279239744339200036313333248 Wave Height	1/30649910817884461196092558479488678400072626666496 Wave Height	1/61299821635768922392185116958977356800145333331984 Wave Height	1/12259964327153784478437023391795471136002906666696 Wave Height	1/24519928654307568956874046783589422720058133333392 Wave Height	1/4903985730861513791374809356717884544011626666684 Wave Height	1/9807971461723027582749618713435769088023253333368 Wave Height	1/1961594292444605516549923742687153817604650666676 Wave Height	1/392318858488921103309984748537430763521301333352 Wave Height	1/784637716977842206619969497074861530842602666704 Wave Height	1/1569275433955684413239938994149723161685205333408 Wave Height	1/3138550867911368826479877888299446323370410666816 Wave Height	1/6277101735822737652959755776598896446740821333632 Wave Height	1/12554203471645475305919511553197792893481642666864 Wave Height	1/25108406943290950611839023106395585786963285333728 Wave Height	1/50216813886581901223678046212791171573926570667456 Wave Height	1/100433627773163802447356092425582343547853141334912 Wave Height	1/200867255546327604894712184851164687095706282669824 Wave Height	1/40173451109265520978942436970232937419141256533952 Wave Height	1/80346902218531041957884873940465874838282513067904 Wave Height	1/160693804437062083915769747880931748775765026138176 Wave Height	1/321387608874124167831539495761863497551530052276352 Wave Height	1/642775217748248335663078991523726995103060104552704 Wave Height	1/1285550435496496671326157983047453990206120209105408 Wave Height	1/2571100870992993342652315966094907980412404182210816 Wave Height	1/514220174198598668530463193218981596082480836442132 Wave Height	1/10284403483971973370609263864379631921649616728842624 Wave Height	1/205688069679439467412185277287592638432992334576848 Wave Height	1/411376139358878934824370554575185276865984671553696 Wave Height	1/822752278717757869648741109150370553731969343107392 Wave Height	1/1645504577435515739297482218307541107463938686214784 Wave Height	1/329100915487103147859496443661508221492787737243568 Wave Height	1/658201830974206297018992887323016439965575474487136 Wave Height	1/1316403661948412594037985774646032879931150948974272 Wave Height	1/2632807323896825188075971549292065759862301897948544 Wave Height	1/5265614647793650376151943098584131519724603795897088 Wave Height	1/10531229295587300752303886197168263039449207591794176 Wave Height	1/2106245859117460150460777239433652607889841518358832 Wave Height	1/4212491718234920300921554478867305215779683036717664 Wave Height	1/842498343646984060184310895773461031555936607343328 Wave Height	1/1684996687293968120368621791546922063111872124686656 Wave Height	1/3369993374587936240737243583093844126223744249373312 Wave Height	1/6739986749175872481474487166187688252447488498746624 Wave Height	1/1347997353835174494294897433237537650489497699749248 Wave Height	1/2695994707670348988589794866475075300978995399498496 Wave Height	1/5391989415340697977179590732950150601957990798996992 Wave Height	1/10783978830681395954359181465900303203915935997993984 Wave Height	1/21567957661362791908718362931800606407831871995987968 Wave Height	1/43135915322725583817436725863601212815663743991975936 Wave Height	1/86271830645451167354873451727202425631327487983951872 Wave Height	1/172543661290902334709746903454404852622654959967903744 Wave Height	1/345087322581804669419493806908809705245309919935807488 Wave Height	1/690174645163609338838987613817619410480619839871614976 Wave Height	1/1380349290327218677677975227635238820961316799743229728 Wave Height	1/2760698580654437355355950455270477641922633599486459456 Wave Height	1/5521397161308874710711900910540954839845267198972918912 Wave Height	1/11042794322617749421423801821081909679690534397945837824 Wave Height	1/22085588645235498842847603642163819399381068795891673648 Wave Height	1/44171177290470997685695272884327638798762137591783347392 Wave Height	1/88342354580941995371390545768655277597524275183566684672 Wave Height	1/176684709161883990742781091537110555195048550367133331344 Wave Height	1/35336941832376798148556218307422111039009710073426666688 Wave Height	1/70673883664753596297112436614844222078019420146853333376 Wave Height	1/141347767329507192594224873229688444156038840293706666752 Wave Height	1/282695534659014385188449746459376888312077680587413333504 Wave Height	1/56539106931802877037689949291875377662415376117482666808 Wave Height	1/113078213863605754075379898583750753324830752234965333616 Wave Height	1/22615642772721150815075979716750150644966150446933066832 Wave Height	1/45231285545442301630151959433500301289932208913866133664 Wave Height	1/90462571090884603260303918867000602579864417827732267328 Wave Height	1/18092514218176920652060783773400120559972883565546445456 Wave Height	1/36185028436353841304121567546800241119945767131092890912 Wave Height	1/72370056872707682608243135093600482399891534262185781824 Wave Height	1/144740113745415365216486270187200964799782685243715733648 Wave Height	1/289480227490830730432972540374401935999565370487431467936 Wave Height	1/578960454981661460865945080748803871999130740974862895872 Wave Height	1/1157920909963322921731890161496077439982261419549725771544 Wave Height	1/231584181992664584346378032299215487996452283909945152896 Wave Height	1/463168363985329168692756064598430975992904567819890305792 Wave Height	1/926336727970658337385512129196861951985809135639780711584 Wave Height	1/185267345594131667477102425839372391597161831267956143168 Wave Height	1/370534691188263334954204851678744783194323662535912286336 Wave Height	1/741069382376526669908409703357489566388647325071824572672 Wave Height



Figure 2. The "Sandgrabber" in Lake Erie



Figure 3. Campbell's precast breakwater units



Figure 4. Gobi blocks in the large wave tank at CERC



Figure 5. "Goodyear" type floating breakwater, Cranston, Rhode Island



Figure 6. Sand filled bags as a revetment in conjunction with an asbestos bulkhead and dune vegetation at Seabrook Island, South Carolina



Figure 7. Institutional low-cost measures



Figure 8. Bolsaroca, large, reinforced, synthetic bags filled with mortar or concrete in sites



Figure 9. The Shoreprotector, at Virginia Beach, Virginia

SHORELINE EROSION CONTROL DEMONSTRATION PROGRAM

The Congress finds that because of the importance and increasing interest in the coastal and estuarine zone of the United States, the deterioration of the shoreline within this zone due to erosion, the harm to water quality and marine life from shoreline erosion, the loss of recreational potential due to such erosion, the financial loss to private and public landowners resulting from shoreline erosion, and the inability of such landowners to obtain satisfactory financial and technical assistance to combat such erosion, it is essential to develop, demonstrate, and disseminate information about low-cost means to prevent and control shoreline erosion. It is therefore the purpose of this section to authorize a program to develop and demonstrate such means to combat shoreline erosion.

Thus on March 7, 1974, the President signed into law Section 54, Public Law 251, 93rd Congress -- the Shoreline Erosion Control Demonstration Act of 1974. The Act calls for the Chief, U.S. Army Corps of Engineers, to plan, establish, and conduct for a period of five years a national shoreline erosion control demonstration and development program. The program consists of planning, constructing, maintaining, evaluating and demonstrating prototype shoreline erosion control devices, both physical and vegetative. The Act is silent on institutional devices and these are, therefore, omitted from the program.

Although the Corps of Engineers is administering the project, they are cooperating with the Department of Agriculture, vis-a-vis the Soil Conservation Service, particularly with respect to vegetative means of preventing and controlling shoreline erosion.

The actual demonstration projects developed under this program emphasize the development of low-cost erosion control devices on sheltered or inland waters. These demonstration projects are being constructed with at least two sites each on the shorelines of the Atlantic, Gulf, and Pacific Coasts, the Great Lakes, and the State of Alaska, and with six sites at serious erosion sites in the State of Delaware along Delaware Bay. These demonstration projects can be built on private or public lands as long as a non-federal sponsor can pay at least 25 percent of the construction costs and assume operation and maintenance costs upon completion of the project.

The Act directed the Chief of Engineers to establish the Shoreline Erosion Advisory Panel. The Panel is charged with providing general guidance and expert technical advice to the Chief on the establishment, conduct, and evaluation of results of the program. The Panel consists of 15 members, selected as individuals who are knowledgeable with respect to various aspects of shoreline erosion problems. Representatives from various geographical areas, institutions of higher education, professional organizations, state and local government and private organizations serve on the Panel. Specifically, the Panel is to:

- (a) advise the Chief of Engineers generally in carrying out provisions of this Act;
- (b) recommend criteria for the selection of development and demonstration sites;
- (c) recommend alternative institutional, legal, and financial arrangements necessary to effect agreements with non-Federal sponsors of project sites;
- (d) make periodic reviews of the progress of the program pursuant to this section;
- (e) recommend means by which the knowledge obtained from the project may be made readily available to the public; and
- (f) perform such functions as the Chief of Engineers may designate.

To carry out this program, Congress has authorized appropriations, over the five-year life of the program, not to exceed \$8,000,000.

A demonstration site is a shore frontage occupied by shore protection works consisting of one or more installations or devices to be monitored and evaluated under the SEAP program. The site shall include the area containing the installation or installations, plus adjacent shore fronts likely to be significantly affected by them within ten years of the date of installation. It is further recognized that three types of sites may be used.

- (a) SEAP Site - A site on which installation of protective works are initiated under the SEAP program.
- (b) Joint Site - A site bearing existing shore protection works constructed by others but which are repaired, modified, or supplemented under the SEAP program.
- (c) Existing Site - A site containing existing shore protection works or devices installed by others, but selected for study and evaluation under the SEAP program.

The Panel has developed and adopted a set of criteria for site selection evaluation which considers legal criteria, social and public relations criteria, environmental criteria, and economic criteria. The Panel has also developed and adopted a procedure for site selection; this procedure involves identifying candidate sites and ranking them in order of value as regional demonstration sites, and then matching these sites with a priority listing of methods and devices which the Panel believes worthy of testing. The result is a program of test installations scheduled as to costs and year of installation; the recommended program has been sent by the Panel to the Chief of Engineers with recommendations for construction.

The enabling Act requires that when a demonstration project is installed on non-Federal property, that part of the expense be borne by an agency or individual other than the Federal government. The Panel has prepared a set of recommendations on institutional arrangements which will be forwarded to the Chief of Engineers in October 1976. Among the questions considered in the institutional arrangements are: access to demonstration site by the interested public; liability of Federal government and land-owners for damage to other persons or other property; duration of demonstration testing at the particular site; removal of unsuccessful devices at the end of demonstration period.

The Panel has also addressed the question of monitoring the demonstration sites once the devices have been installed. As a result of its deliberations, the Panel has a draft of guidelines for use in monitoring test installations. The draft guidelines include coverage of such subjects as the proper balance between the number and type of monitoring observations against the expense of the monitoring program, and whether or not a device will be repaired or modified, and to what extent, if it is found to be failing in its intended protective action.

In accordance with the Act, the Chief of Engineers has announced the following sixteen sites (including six in Delaware Bay) where demonstration projects will be constructed.

Kotzabue, Alaska	Slaughter Beach, Delaware
Unalaklett, Alaska	Basin Bayou State Park, Florida
Alameda, California	Stuart-Jensen Causeways, Florida
Bowers, Delaware	Geneva State Park, Ohio
Broadkill Beach, Delaware	Bulls Island, South Carolina
Kitts Hummock, Delaware	Sand Point, Texas
Lewes, Delaware	Oak Harbor, Washington
Pickering Beach, Delaware	Port Wing, Wisconsin

This list includes private, local, state, and federal lands. Moreover, it includes sandy, clay, and cobble beaches, coasts with bluffs and those with dunes, beaches with moderate wave energy and beaches with low wave energy, and beaches frequented by ice. These sites are representative of the U.S. coastline.

The success of this program will do much to bring realistic, workable, low-cost shoreline protection solutions into the hands of local government and most importantly the private landowner.

ACKNOWLEDGEMENTS

The authors wish to acknowledge those members of private industry, the Soil Conservation Service, the Corps of Engineers, and especially the members of the Shoreline Erosion Advisory Panel who have significantly contributed to the concepts and activities described in this paper. This paper reflects only the views of the authors and is not intended to represent the position of any body or institution.

REFERENCES

- Armstrong, J. M. "Demonstration Project for Low-Cost Protection," Proceedings Fifteenth Coastal Engineering Conference, ASCE (1976).
- Arno, N. "Help Yourself: A Discussion of the Critical Erosion Problems on the Great Lakes and Alternative Methods of Shore Protection," U.S. Army Corps of Engineers, North Central Division, Chicago (1973).
- Brater, E. F. "Low-Cost Shore Protection for the Great Lakes," Lake Hydraulic Lab, University of Michigan, Ann Arbor, reprinted in 1975 (1952).
- Brater, E. F., J. M. Armstrong and M. McGill "Michigan's Demonstration and Erosion Control Program: Update Evaluation Report - August 1975," Coastal Zone Lab, University of Michigan, Ann Arbor (1975).
- Combe, A. J., III and D. W. Berg "Guidelines for Monitoring Shore Protection Structures in the Great Lakes," U.S. Army Corps of Engineers, Coastal Engineering Research Center, Working Paper (1974).
- Dahl, B. E., et al. "Construction and Stabilization of Coastal Foredunes with Vegetation; Padre Island, Texas," MP 9-75, U.S. Army Corps of Engineers, Coastal Engineering Research Center (1975).
- Davis, J. H., Jr. "Stabilization of Beaches and Dunes by Vegetation in Florida," Report No. 7, Florida Sea Grant Program, Gainesville (1975).
- Habel, J. F. "Shore Protection in California," Department of Navigation and Ocean Development, State of California, Sacramento (1976).
- McHarg, I. "Best Shore Protection: Nature's Own Dunes," Civil Engineering, September (1972).
- O'Shaughnessy, M. M. "Ocean Beach Esplanade, San Francisco, California," Transactions, ASCE (1924).
- Seneca, E. D., W. W. Woodhouse, Jr., and S. W. Broome "Dune Stabilization with Panicum Amarum Along the North Carolina Coast," MR 76-3, U.S. Army Corps of Engineers, Coastal Engineering Research Center (1976).
- Soil Conservation Service "Vegetative Tidal Bank Stabilization," U.S. Department of Agriculture, College Park, Maryland (1968).
- Webb, J. W. and J. D. Dodd "Vegetation Establishment and Shoreline Stabilization: Galveston Bay, Texas," TP 76-13, U.S. Army Corps of Engineers, Coastal Engineering Research Center (1976).
- Woodhouse, W. W., E. D. Seneca, and S. W. Broome "Propagation of Spartina Alterniflora for Substrate Stabilization and Salt Marsh Development," TM 46, U.S. Army Corps of Engineers, Coastal Engineering Research Center (1974).